



Versatech 1100 ULB

Bariatric Ultra-Low Bed



Technical specifications

Platform width:	Adjustable from 35" to 38" to 41" to 47" to 53" (89 cm to 97 cm to 104 cm to 119 cm to 134 cm)
Overall width at 35":	40" (101 cm)
Overall width at 53":	57" (144 cm)
Platform length:	80" to 84" to 88" (203 cm to 213 cm to 223 cm)
Overall length at 80":	93 1/8" (237 cm)
Overall length at 88":	101 1/8" (257 cm)
Minimum height:	8" (21 cm)

Maximum height:	32" (81 cm)
Load capacity:	1100 lb (499 kg)
Backrest angle:	70°
Footrest angle:	34°
Trendelenburg position:	-14° to +14° (degrees)
Under bed clearance:	5 1/8" (14,9 cm)
Bed weight:	438 lb (199 kg)

Features

- Easily expandable in width (press buttons) that can accommodate mattresses of 36", 39", 42"48" and even 54"
- Load capacity of 1100 lb (499 kg) for bariatric use
- Prevent Falls Related Injuries: 8" (21 cm) Ultra-Low Bed
- Ultra quiet DC motors. Helps maintain a calm and relaxed environment
- Emergency battery for temporary autonomy
- Easy to maintain with quick connect components
- Central brake: one pedal at the foot of the bed
- Lightweight composite head and footboard for ease of use.
- Antimicrobial and easy to clean powder coated steel structure
- 5" (125mm) anti-static double wheels casters
- 2 pairs of half-length composite siderails
- · Patient remote control with auto-contour
- Patient control integrated into the bed siderails with auto-contour, underbed light and nurse call
- Nurse call built into the siderails with DB-37 connexion
- Easy to use nurse control integrated in the footboard
- Bed functions lock-out from the nurse control at the footboard
- Side and foot mattress retainer
- Backrest angle indicator
- Easily extendable in length without tools from 80" to 84" to 88" (203 cm to 213 cm to 223 cm)
- One-touch Trendelenburg adjustment
- Night light
- Multiple openings for restraint straps
- Bumpers at the head of the bed
- IV pole holders
- Trapeze bar receptacle
- Electric CPR
- Mechanical CPR: 2 handles
- Authentic Canadian product
- CSA certified according to Canadian and American standards.

Options

 Integrated scale with 2 zones bed exit notification, integrated warning signal to DB-37 port with visual and audible indicator

Accessories

- Bar with trapeze
- IV pole
- Left retractable IV pole
- Right retractable IV pole
- Support for oxygen cylinder
- Pump support
- DB-37 adapter cable
- Additional remote control
- Bed trolley
- Siderail protectors
- Mattress length extension 4"
- Mattress V1100 with 3 width extension

Electronic

- Voltage: 120 V AC
- Amperage: 4 A
- Frequency: 60Hz
- Leakage current: <300 microamps
- Battery: 1.2aH sealed lead acid, 2 x 12V
- Scale accuracy (regardless of the bed position): 1% of the patient weight













10001 April 1 2021 9:56 AM









Technical specifications

Platform width:	Adjustable from 35" to 38" to 47" to 53" (89 cm to 97 cm to 119 cm to 134 cm)
Platform length:	78" (198 cm)
Minimum height:	13" (33 cm) or 13 $\frac{1}{2}$ " (34 cm) for fixed base
Maximum height:	30" (76 cm) or 30 $\frac{1}{2}$ " (77 cm) for fixed base
Load capacity:	1100 lb (499 kg)

Maximum backrest angle:	64° (degrees)
Maximum footrest angle:	36° (degrees)
Trendelenburg Position:	-14° to +14° (degrees)
Dégagement sous le lit :	Variable according to the height of the bed: 6" (12 cm) clearance when bed is 17" high (43 cm)
Bed weight:	309 lb (140 kg)

Accessories

- Composite or melamine decorative headboard and footboard (Choice of melamine colors: white, rosewood, maple, and other colors on request)
- Rotec tilt-up half side rails 28" (71 cm)
- Rotec rotating half side rails 28" (71 cm)
- Rotec rotating half side rails with increased protection height 28" (71 cm)
- IV pole
- Bed trolley
- Bar with trapeze
- Siderail pad
- Pump support
- V1100 mattress in 3 pieces

Features

- Bed designed for home care patients or long-term care facilities
- Bed with the highest load capacity in its category
- Affordable width-adjustable bariatric bed
- Ultra quiet DC motors. Helps maintain a calm and relaxed environment.
- Width-adjustable bed platform that does not require tools
- Battery ensuring temporary autonomous operation
- IP54-approved electrical components protected from dust and water infiltration
- Bed can bed moved at any heights even when in its lowest position
- Composite platform spring cover
- Antimicrobial and easy to clean powder coated steel structure
- Casters equipped with a synchronized braking system (2 x 2 casters)
- 4" / 10 cm diameter medical casters
- 8 functions remote control
- Manually adjustable foot section angle (choice of three positions: flexion, standard and extension)
- Side and foot mattress retainer
- 6 receptacles for IV pole
- Bumpers at the head and foot end of the bed
- Bed may be separated into two sections to facilitate transport
- Authentic Canadian product

Options

- Digital nurse control integrated in the footboard (include the head and footboard)
- Digital patient control integrated in the siderails (requires the nurse control, include one pair of siderail)
- Length extension of the platform to 88 ½" (225 cm)
- Fixed base











